

## RV-200 Series Rotary Evaporators

- Unique PTFE sealing system offers excellent thermostability
- PID temperature controller provides stable temperature control
- Small footprint takes up minimal lab space
- Choose simple one-handed manual lift or automatic motorized lift
- 3-year warranty



RV-200 with manual lift



RV-200 with motorized lift

## RV-200 Series Rotary Evaporators

Our RV-200 series rotary evaporators focus on essential features to support your everyday lab processes. Easily set and view operating parameters on the two large digital displays; one for rotation speed and timer and another for bath temperature and timer. The unique PTFE sealing system provides great thermostability plus excellent chemical and corrosion resistance.

Stainless steel bath features PTFE coating to withstand high temperatures and is easy to clean. Safety features include dry-run protection, over-temperature shutoff, circuit breaker, and power interruption alarm.

Each unit includes evaporator control stand, uncoated glassware set (vertical condenser, 1-L sample flask, 1-L receiving flask), clip, water bath, vacuum gauge, and power cords (NEMA 5 plugs for 120 VAC models; NEMA 6 plugs for 220 VAC models) for rotator and bath.

### Specifications

Model no.	RV-200
Rotation speed	20 to 300 rpm
Speed resolution	1 rpm
Water bath temp range	5 to 99 °C
Temperature resolution	0.1 °C
Evaporation rate	22 mL/min
Maximum vacuum	8 mbar
Vacuum connection	Angled 10 mm GL14 barb
Display	Two LCDs
Timer range	1 to 5999 minutes
Dimensions (W x H x D)	57.0 x 75.4 x 38.6 cm (22.4 x 29.7 x 15.2 in)
Warranty	3 years

### Ordering Information

Max evaporation flask size*	Lift mechanism	Wattage	Power (50/60 Hz)	Item no.	Model no.
2 L	Manual	1000 W	120 VAC	52411-92	RV-200-2-120
			220 VAC	52411-93	RV-200-2
2 L	Motorized	1000 W	120 VAC	52411-94	RV-200A-2-120
			220 VAC	52411-95	RV-200A-2

\*Unit is provided with a 1-L evaporation flask but accommodates either a 1-L or 2-L flask.

coleparmer.com

USA:  
+1.800.323.4340  
+1.847.549.7600

Canada: +1 800 363 5900  
China: +86 21 5109 9909  
France: +33 (0)1 48 63 78 00  
Germany: +49 (0) 9377 92030

India: +1 800 266 1244  
Italy: +39 (0)2 84349215  
UK: +44 (0) 1480 272279  
All other countries: +1 847 549 7600

**Cole-Parmer®**